



Spare parts for:
Consumables



Electronic thermostats and controllers



This catalogue is automatically generated.
Therefore, the sequence of the items might
not be always shown at best.
Updates will be issued in case of additions
and/or amendments.





Electronic thermostats and controllers



Suitable for:

Suitable for:

3445043 PRESSURE SWITCH ELIWELL IC915LX/P
 230V 50/60Hz
 2 relay outputs 8A
 BAR pressure scale
 selectable input: 0-20 mA or 4-20 mA
 selectable decimal point
 front dimension 32x74xdepth 60 mm



3445052 PRESSURE PROBE FWPA 007
 operating field -0.5+8 bar
 current output 4..20 mA
 connection with 2000 mm cable
 pressure connection 1/4"sae M
 power supply 8..32 V cc



3445053 PRESSURE PROBE EWPA 030
 operating field 0/+30 bar
 current output 4..20 mA
 connection with 2000 mm cable
 pressure connection 1/4"sae M
 power supply 8..32 V cc



3445044 HUMIDITY REGULATOR ELIWELL IC912/R
 230V 50/60Hz
 1 relay output 8A
 relative humidity scale %RH
 selectable input: 0-20 mA or 4-20 mA
 selectable decimal point
 front dimension 32x74xdepth 60 mm



3445051 HUMIDITY PROBE EWHS 284
 dimensions 103x25 mm
 operating temperature -10+60°C
 humidity measurement range 15/90% RH
 output signal 4-20 mA
 power supply 9/28V
 humidity resistive sensor



3445066 CONTROLLER ELIWELL ID975LX
 12Vac/dc
 1 relay output 8A for compressor
 1 relay output 8A for defrosting
 1 relay output 5A for evaporator fans
 1 relay outlet 5A for alarm/light
 2 selectable NTC/PTC probes (not included)
 internal buzzer and serial port
 front dimension 74x32xdepth 67 mm
 mounting hole 71x29 mm



3445067 CONTROLLER ELIWELL ID985LX CK
 12Vac/dc
 1 relay output 8A for compressor
 1 relay output 8A for defrosting
 1 relay output 8A for evaporator fans
 1 relay outlet 5A for alarm/light
 2 programmable digital inputs
 3 selectable NTC/PTC probes (not included)
 LINK- and LINK+ connection
 with RTC function
 TTL serial door
 front dimension 74x32xdepth 67 mm
 mounting hole 71x29 mm





Electronic thermostats and controllers



Suitable for:

Suitable for:

3445078 CONTROLLER ELIWELL IWC750
 230V 50/60Hz
 depth 69 mm (without terminals)
 1 relay output 16A for compressor
 1 relay output 20A for defrosting
 1 relay output 8A for fans
 1 relay output 8A for alarm
 1 relay output 8A for aux/light
 2 NTC probes (not included)
 terminals not included
 TTL input for copy card or TELEVIS system
 mounting hole 150x31 mm
 front dimension 180x37 mm

3445319 FEMALE TERMINAL BLOCK KIT FOR IWC750




3445079 CONTROLLER ELIWELL IWC720 SHORT
 230V 50/60Hz
 depth 45 mm
 1 relay output 16A for compressor - faston 6.3 mm
 1 relay output 8A for light - faston 6.3 mm
 1 NTC probe (not included) - faston 2.8 mm
 1 programmable digital input - faston 2.8 mm
 TTL input f/copy card or TELEVIS system connection
 mounting hole 150x31 mm
 front dimension 180x37 mm

3445064 PROBE NTC 1500 mm faston 2.8 mm
 temperature range -30°+80°C



3445085 CONTROLLER ELIWELL IWC730 SHORT
 230V 50/60Hz
 depth 45 mm
 1 relay output 16A for compressor - faston 6.3 mm
 1 relay output 20A for defrosting - faston 6.3 mm
 1 relay output 8A for fans - faston 6.3 mm
 2 NTC probes (not included) - faston 2.8 mm
 1 programmable digital input - faston 2.8 mm
 TTL input f/copy card or TELEVIS system connection
 mounting hole 150x31 mm
 front dimension 180x37 mm

3445064 PROBE NTC 1500 mm faston 2.8 mm
 temperature range -30°+80°C





Electronic thermostats and controllers



Suitable for:

Suitable for:

3445088 CONTROLLER ELIWELL IC915LX

12Vac/dc
2 dependent/independent relay outputs 8A or
with neutral zone with parameter setting
1 NTC/PTC probe
TTL serial port



3445089 CONTROLLER ELIWELL IC915LX

230V 50/60Hz
2 dependent/independent relay outputs 8A or
with neutral zone with parameter setting
1 NTC/PTC probe
TTL serial port



3445070 PTC PVC PROBE 1500 mm

2-wire probe temperature range -30+80°C
bulb ø 6x40 mm



3445157 PROBE NTC PVC 1500 mm

temperature range -30°+80°C
bulb ø 6x40 mm



3445161 CONTROLLER AKO D14112

12-24Vac/dc 50/60Hz
1 relay output 12A
complete with NTC probe
mounting dimensions 71x29x62 mm



3445162 CONTROLLER AKO D14123

230V 50/60Hz
1 relay output 12A for compressor
complete with NTC probe
mounting dimensions 71x29x43 mm





Electronic thermostats and controllers



Suitable for:

Suitable for:

3445163 CONTROLLER AKO D14212
 12Vac/dc 50/60Hz
 1 relay output 12A for compressor
 1 relay output 8A for aux
 complete with NTC probe
 mounting dimensions 71x29x62 mm




3445164 CONTROLLER AKO D14323
 230V 50/60Hz
 1 relay output 16A for compressor
 1 relay output 8A for defrosting
 1 relay output 6A for ventilator
 complete with NTC probe
 mounting dimensions 71x29x62 mm



3445170 CONTROLLER DIXELL XR20CX-0N0C1
 12Vac/dc
 1 relay output 20A for compressor
 1 programmable digital input (clean contact)
 pause defrosting
 selectable NTC/PTC probe (not included)
 front dimension 78x37 depth 60 mm
 mounting hole 71x29 mm
 Hot Key/TTL serial output



3445171 CONTROLLER DIXELL XR20CX-5N0C1
 230V
 ON-OFF control with 1 actuation point
 1 relay output 20A for compressor
 1 programmable digital input (clean contact)
 pause defrosting
 selectable NTC/PTC probe (not included)
 front dimension 78x37x60 mm
 mounting hole 71x29 mm
 Hot Key/TTL serial output



3445172 CONTROLLER DIXELL XR30CX-0N0C1
 12Vac/dc
 1 relay output 20A for compressor
 1 relay output 8A for alarm
 1 programmable digital input (clean contact)
 pause defrosting
 selectable NTC/PTC probe (not included)
 front dimension 78x37 depth 60 mm
 mounting hole 71x29 mm
 Hot Key/TTL serial output



3445070 PTC PVC PROBE 1500 mm
 2-wire probe temperature range -30+80°C
 bulb ø 6x40 mm



3445107 PTC PVC PROBE 3000 mm
 2-wire probe temperature range -30+80°C
 bulb ø 6x40 mm



3445154 PROBE NTC IP68 3000 mm
 temperature range -40+110°C
 bulb ø 6x40 mm watertight





Electronic thermostats and controllers



Suitable for:

3445155 SILICONE PROBE NTC 3000 mm
temperature range $-50^{\circ}+110^{\circ}\text{C}$
bulb \varnothing 6x40 mm



Suitable for:

3445156 PROBE NTC PVC 3000 mm
temperature range $-30^{\circ}+80^{\circ}\text{C}$
bulb \varnothing 6x40 mm



3445157 PROBE NTC PVC 1500 mm
temperature range $-30^{\circ}+80^{\circ}\text{C}$
bulb \varnothing 6x40 mm



3445167 PROBE NTC IP68 1500 mm
temperature field $-50^{\circ}+110^{\circ}\text{C}$
bulb \varnothing 6x20 mm watertight



3445183 SILICONE PTC PROBE 3000 mm
2-wire probe temperature range $-55+150^{\circ}\text{C}$
bulb \varnothing 6x40 mm



3445184 PROBE NTC PVC 1500 mm IP68
temperature range $-40^{\circ}+110^{\circ}\text{C}$
bulb \varnothing 6x40 mm watertight



3445335 PROBE NTC IP68 3000 mm
temperature range $-50+110^{\circ}\text{C}$
bulb \varnothing 6x15 mm watertight



3445913 SILICONE PROBE NTC 1500 mm
temperature range $-50+110^{\circ}\text{C}$
bulb \varnothing 6x40 mm



3445959 SILICONE PTC PROBE 5000 mm
temperature range $-55^{\circ}+150^{\circ}\text{C}$
bulb \varnothing 6x40 mm





Electronic thermostats and controllers



Suitable for:

Suitable for:

3445173 CONTROLLER DIXELL XR30CX-5N0C1
 230V
 1 relay output 20A for compressor
 1 relay output 8A for alarm
 1 programmable digital input (clean contact)
 pause defrosting
 selectable NTC/PTC probe (not included)
 front dimension 78x37 depth 60 mm
 mounting hole 71x29 mm
 Hot Key/TTL serial output



3445070 PTC PVC PROBE 1500 mm
 2-wire probe temperature range -30+80°C
 bulb ø 6x40 mm



3445107 PTC PVC PROBE 3000 mm
 2-wire probe temperature range -30+80°C
 bulb ø 6x40 mm



3445154 PROBE NTC IP68 3000 mm
 temperature range -40°+110°C
 bulb ø 6x40 mm watertight



3445155 SILICONE PROBE NTC 3000 mm
 temperature range -50°+110°C
 bulb ø 6x40 mm



3445156 PROBE NTC PVC 3000 mm
 temperature range -30°+80°C
 bulb ø 6x40 mm



3445157 PROBE NTC PVC 1500 mm
 temperature range -30°+80°C
 bulb ø 6x40 mm



3445167 PROBE NTC IP68 1500 mm
 temperature field -50°+110°C
 bulb ø 6x20 mm watertight



3445183 SILICONE PTC PROBE 3000 mm
 2-wire probe temperature range -55+150°C
 bulb ø 6x40 mm



3445184 PROBE NTC PVC 1500 mm IP68
 temperature range -40°+110°C
 bulb ø 6x40 mm watertight





Electronic thermostats and controllers



Suitable for:

3445335 PROBE NTC IP68 3000 mm
temperature range -50+110°C
bulb ø 6x15 mm watertight



Suitable for:

3445913 SILICONE PROBE NTC 1500 mm
temperature range -50+110°C
bulb ø 6x40 mm




3445959 SILICONE PTC PROBE 5000 mm
temperature range -55°+150°C
bulb ø 6x40 mm



3445174 CONTROLLER DIXELL XR40CX-0N0C1
12Vac/dc
1 relay output 20A for compressor
1 relay output 8A for defrosting
1 programmable digital input (clean contact)
2 selectable NTC/PTC probes (not included)
front dimension 78x37 depth 60 mm
mounting hole 71x29 mm
Hot Key/TTL serial output



3445175 CONTROLLER DIXELL XR40CX-5N0C1
230V
1 relay output 20A for compressor
1 relay output 8A for defrosting
1 programmable digital input (clean contact)
2 selectable NTC/PTC probes (not included)
front dimension 78x37 depth 60 mm
mounting hole 71x29 mm
Hot Key/TTL serial output



3445178 CONTROLLER DIXELL XW20LS-5N0C1 SHORT
230V
depth 48 mm
1 relay output 20A for compressor - faston 6.3 mm
1 relay output 8A for light - faston 6.3 mm
1 NTC/PTC probe (not included) - faston 2.8 mm
front dimension 185x38 mm
mounting hole 150x31 mm



3445179 CONTROLLER DIXELL XW60LS-5N0C1 SHORT
230V
depth 48 mm
1 relay output 20A for compressor - faston 6.3 mm
1 relay output 8A for defrosting - faston 6.3 mm
1 relay output 8A for fans - faston 6.3 mm
2 NTC/PTC probes (not included) - faston 2.8 mm
front dimension 185x38 mm
mounting hole 150x31 mm





Electronic thermostats and controllers



Suitable for:

Suitable for:

3445180 CONTROLLER DIXELL XW20L-5N0C1
 230V
 depth 76 mm
 1 relay output 20A for compressor - faston 6.3 mm
 1 relay output 8A for light - faston 6.3 mm
 1 NTC/PTC probe (not included)
 1 programmable digital input
 front dimension 185x38 mm
 mounting hole 150x31 mm



3445181 CONTROLLER DIXELL XW60L-5N0C1
 230V
 depth 76 mm
 1 relay output 20A for compressor - faston 6.3 mm
 1 relay output 8A for defrosting - faston 6.3 mm
 1 relay output 8A for fans - faston 6.3 mm
 1 relay output 8A for light - faston 6.3 mm
 2 NTC/PTC probes (not included)
 1 programmable digital input
 front dimension 185x38 mm
 mounting hole 150x31 mm



3445182 CONTROLLER DIXELL XW20VS-5N0C0
 230V
 depth 40 mm
 1 relay output 16A for compressor - faston 6.3 mm
 1 relay output 8A for light - faston 6.3 mm
 2 NTC/PTC probes (not included) - faston 2.8 mm
 1 programmable digital input - faston 2.8 mm
 front dimension 100x64 mm
 mounting hole 56x72 mm



3445197 CONTROLLER DIXELL XW30L-00000 SHORT
 230V
 depth 48 mm
 1 relay output 20A for compressor - faston 6.3 mm
 1 relay output 8A for fans - faston 6.3 mm
 1 relay output 8A for light - faston 6.3 mm
 2 NTC probes (not included) - faston 2.8 mm
 front dimension 185x38 mm
 mounting hole 150x31 mm



3445207 CONTROLLER DIXELL XR04CX-5N0C1
 230V
 1 relay output 20A for compressor
 1 relay output 8A for evaporator fan
 1 programmable digital input (clean contact)
 pause defrosting
 2 selectable NTC/PTC probes (not included)
 front dimension 78x37 depth 55 mm
 mounting hole 71x29 mm
 Hot Key/TTL serial output



3445230 CONTROLLER DIXELL XW40L-5N0C1
 230V
 depth 76 mm
 1 relay output 20A for compressor - faston 6.3 mm
 1 relay output 8A for defrosting - faston 6.3 mm
 1 relay output 8A for light - faston 6.3 mm
 2 NTC/PTC probes (not included)
 1 programmable digital input
 front dimension 185x38 mm
 mounting hole 150x31 mm





Electronic thermostats and controllers



Suitable for:

Suitable for:

3445231 CONTROLLER DIXELL XW260L-5N0C5

power supply 230V
 depth 76 mm
 1 relay output 20A for compressor
 1 relay output 8A for defrosting
 1 relay output 8A for fans
 1 relay output 16A for light
 3 NTC probes (not included)
 1 door microswitch digital input
 1 programmable digital input
 output for remote display X-REP
 TTL serial output RS485
 front dimension 185x38 mm
 mounting hole 150x31 mm



3445236 CONTROLLER DIXELL XW40LS-5N0C1 SHORT

230V
 depth 48 mm
 1 relay output 20A for compressor - faston 6.3 mm
 1 relay output 8A for defrosting - faston 6.3 mm
 1 relay output 8A for light - faston 6.3 mm
 2 NTC/PTC probes (not included) - faston 2.8 mm
 1 programmable digital input
 front dimension 185x38 mm
 mounting hole 150x31 mm




3445237 CONTROLLER DIXELL XW271L-5N0C1

230V
 depth 76 mm
 1 relay output 20A for compressor
 1 relay output 8A for defrosting
 1 relay output 8A for fans
 1 relay output 16A for light
 1 relay output 8A for alarm
 1 relay output 16A for demisting heating elements
 1 digital input for door microswitch
 1 programmable digital input
 3 NTC probes (not included)
 output for X-REP remote display
 front dimension 185x38 mm
 mounting hole 150x31 mm



3445248 CONTROLLER DIXELL XR70CX-0N0C8

12Vac/dc
 1 relay output 16A for compressor
 1 relay output 16A for defrosting
 1 relay output 16A for fans
 1 relay output 16A for light/alarm
 2 selectable NTC/PTC probes (not included)
 1 programmable digital input
 front dimension 78x37 depth 60 mm
 mounting hole 71x29 mm



3445251 CONTROLLER DIXELL XW264L-5N0C5

230V
 depth 76 mm
 1 relay output 20A for compressor
 1 relay output 8A for defrosting 1
 1 relay output 8A for defrosting 2
 1 relay output 8A for fans
 1 relay output 16A for light
 3 NTC probes (not included)
 1 door microswitch digital input
 1 programmable digital input
 output for remote display X-REP
 TTL serial output RS485
 front dimension 185x38 mm
 mounting hole 150x31 mm



3445257 CONTROLLER DIXELL XW220L-5N0C1

230V
 depth 76 mm
 1 relay output 20A for compressor
 1 relay output 16A for light
 2 NTC probes (not included)
 1 door microswitch digital input
 1 programmable digital input
 output for remote display X-REP
 front dimension 185x38 mm
 mounting hole 150x31 mm






Electronic thermostats and controllers



Suitable for:

Suitable for:

3445297 CONTROLLER DIXELL XR60CX-5N0C1
 230V
 1 relay output 20A for compressor
 1 relay output 8A for defrosting
 1 relay output 5A for evaporator fan
 1 programmable digital input (clean contact)
 2 selectable NTC/PTC probes (not included)
 front dimension 78x37 depth 60 mm
 mounting hole 71x29 mm
 Hot Key/TTL serial output



3445070 PTC PVC PROBE 1500 mm
 2-wire probe temperature range -30+80°C
 bulb ø 6x40 mm



3445107 PTC PVC PROBE 3000 mm
 2-wire probe temperature range -30+80°C
 bulb ø 6x40 mm



3445156 PROBE NTC PVC 3000 mm
 temperature range -30+80°C
 bulb ø 6x40 mm



3445157 PROBE NTC PVC 1500 mm
 temperature range -30+80°C
 bulb ø 6x40 mm



3445298 CONTROLLER DIXELL XR60CX-0N0C0
 12Vac/dc
 1 relay output 16A for compressor
 1 relay output 8A for defrosting
 1 relay output 8A for evaporator fan
 1 programmable digital input (clean contact)
 2 selectable NTC/PTC probes (not included)
 front dimension 78x37 depth 60 mm
 mounting hole 71x29 mm
 Hot Key/TTL serial output



3445299 CONTROLLER DIXELL XW35VS-5N0C0
 230V 50/60Hz
 depth 40 mm
 1 relay output 16A for compressor - faston 6.3 mm
 1 relay output 8A for fans - faston 6.3 mm
 1 relay output 16A for light - faston 6.3 mm
 2 NTC/PTC probes (not included) - faston 2.8 mm
 1 programmable digital input - faston 2.8 mm
 front dimension 100x64 mm
 mounting hole 56x72 mm





Electronic thermostats and controllers



Suitable for:

Suitable for:

3445300 CONTROLLER DIXELL XW60VS-5N0C0
 Power: 230V
 230V 50/60Hz
 depth 40 mm
 1 relay output 16A for compressor - faston 6.3 mm
 1 relay output 16A for defrosting - faston 6.3 mm
 1 relay output 8A for fans - faston 6.3 mm
 3 NTC/PTC probes (not included) - faston 2.8 mm
 1 programmable digital input - faston 2.8 mm
 front dimension 100x64 mm
 mounting hole 56x72 mm



3445301 CONTROLLER DIXELL XW60V-5N0C1
 depth 59 mm
 1 relay output 20A for compressor - faston 6.3 mm
 1 relay output 8A for defrosting - faston 6.3 mm
 1 relay output 8A for fans - faston 6.3 mm
 1 relay output 16A for light - faston 6.3 mm
 2 NTC/PTC probes (not included)
 1 programmable digital input
 front dimension 100x64 mm
 mounting hole 56x72 mm



3445322 CONTROLLER DIXELL XW230L-5N0C0
 230V 50/60Hz
 depth 76 mm
 1 relay output 20A for compressor
 1 relay output 16A for light
 1 relay output 16A for aux
 1 relay output 8A for alarm
 1 door microswitch digital input
 1 programmable digital input
 2 NTC probes (not included)
 front dimension 185x38 mm
 mounting hole 150x31 mm



3445375 CONTROLLER ELIWELL ID PLUS 902
 230V 50/60Hz
 1 relay output 8A for compressor
 1 selectable NTC/PTC/PT1000 probe (not included)
 1 programmable digital/temperature input
 TTL input for copy card connection
 front dimension 74x32xdepth 59 mm
 mounting hole 71x29 mm



3445028 PROBE NTC PVC 4000 mm
 temperature field -30°+80°C
 bulb ø 6x20 mm



3445070 PTC PVC PROBE 1500 mm
 2-wire probe temperature range -30+80°C
 bulb ø 6x40 mm



3445107 PTC PVC PROBE 3000 mm
 2-wire probe temperature range -30+80°C
 bulb ø 6x40 mm





Electronic thermostats and controllers



Suitable for:

3445154 PROBE NTC IP68 3000 mm
temperature range $-40^{\circ}+110^{\circ}\text{C}$
bulb \varnothing 6x40 mm watertight



Suitable for:

3445155 SILICONE PROBE NTC 3000 mm
temperature range $-50^{\circ}+110^{\circ}\text{C}$
bulb \varnothing 6x40 mm



3445156 PROBE NTC PVC 3000 mm
temperature range $-30^{\circ}+80^{\circ}\text{C}$
bulb \varnothing 6x40 mm



3445157 PROBE NTC PVC 1500 mm
temperature range $-30^{\circ}+80^{\circ}\text{C}$
bulb \varnothing 6x40 mm



3445167 PROBE NTC IP68 1500 mm
temperature field $-50^{\circ}+110^{\circ}\text{C}$
bulb \varnothing 6x20 mm watertight



3445183 SILICONE PTC PROBE 3000 mm
2-wire probe temperature range $-55+150^{\circ}\text{C}$
bulb \varnothing 6x40 mm



3445184 PROBE NTC PVC 1500 mm IP68
temperature range $-40^{\circ}+110^{\circ}\text{C}$
bulb \varnothing 6x40 mm watertight



3445335 PROBE NTC IP68 3000 mm
temperature range $-50+110^{\circ}\text{C}$
bulb \varnothing 6x15 mm watertight



3445379 PROBE PT1000 PVC 1500 mm IP68
temperature range $-50^{\circ}+110^{\circ}\text{C}$
bulb \varnothing 6x20 mm watertight



3445380 PROBE PT1000 PVC 3000 mm IP68
temperature range $-50^{\circ}+110^{\circ}\text{C}$
bulb \varnothing 6x20 mm watertight



3445913 SILICONE PROBE NTC 1500 mm
temperature range $-50+110^{\circ}\text{C}$
bulb \varnothing 6x40 mm



3445959 SILICONE PTC PROBE 5000 mm
temperature range $-55^{\circ}+150^{\circ}\text{C}$
bulb \varnothing 6x40 mm






Electronic thermostats and controllers



Suitable for:

Suitable for:

3445376 CONTROLLER ELIWELL ID PLUS 961
 230V 50/60Hz
 1 relay output 2Hp for compressor
 1 selectable NTC/PTC/PT1000 probe (not included)
 1 programmable digital/temperature input
 pause defrosting
 TTL input for copy card connection
 front dimension 74x32xdepth 59 mm
 mounting hole 71x29 mm



3445028 PROBE NTC PVC 4000 mm
 temperature field -30°+80°C
 bulb ø 6x20 mm



3445070 PTC PVC PROBE 1500 mm
 2-wire probe temperature range -30+80°C
 bulb ø 6x40 mm



3445107 PTC PVC PROBE 3000 mm
 2-wire probe temperature range -30+80°C
 bulb ø 6x40 mm



3445154 PROBE NTC IP68 3000 mm
 temperature range -40°+110°C
 bulb ø 6x40 mm watertight



3445155 SILICONE PROBE NTC 3000 mm
 temperature range -50°+110°C
 bulb ø 6x40 mm



3445156 PROBE NTC PVC 3000 mm
 temperature range -30°+80°C
 bulb ø 6x40 mm



3445157 PROBE NTC PVC 1500 mm
 temperature range -30°+80°C
 bulb ø 6x40 mm



3445167 PROBE NTC IP68 1500 mm
 temperature field -50°+110°C
 bulb ø 6x20 mm watertight



3445183 SILICONE PTC PROBE 3000 mm
 2-wire probe temperature range -55+150°C
 bulb ø 6x40 mm





Electronic thermostats and controllers



Suitable for:

3445184 PROBE NTC PVC 1500 mm IP68
temperature range $-40^{\circ}+110^{\circ}\text{C}$
bulb \varnothing 6x40 mm watertight



Suitable for:

3445335 PROBE NTC IP68 3000 mm
temperature range $-50^{\circ}+110^{\circ}\text{C}$
bulb \varnothing 6x15 mm watertight



3445379 PROBE PT1000 PVC 1500 mm IP68
temperature range $-50^{\circ}+110^{\circ}\text{C}$
bulb \varnothing 6x20 mm watertight



3445380 PROBE PT1000 PVC 3000 mm IP68
temperature range $-50^{\circ}+110^{\circ}\text{C}$
bulb \varnothing 6x20 mm watertight



3445913 SILICONE PROBE NTC 1500 mm
temperature range $-50^{\circ}+110^{\circ}\text{C}$
bulb \varnothing 6x40 mm



3445959 SILICONE PTC PROBE 5000 mm
temperature range $-55^{\circ}+150^{\circ}\text{C}$
bulb \varnothing 6x40 mm



3445377 CONTROLLER ELIWELL ID PLUS 971
230V 50/60Hz
1 relay output 2Hp for compressor
1 relay output 8A for defrosting
2 selectable NTC/PTC/PT1000 probes (not included)
1 programmable digital/temperature input
1 programmable digital input
TTL input for copy card connection
with buzzer
front dimension 74x32xdepth 59 mm
mounting hole 71x29 mm



3445028 PROBE NTC PVC 4000 mm
temperature field $-30^{\circ}+80^{\circ}\text{C}$
bulb \varnothing 6x20 mm



3445070 PTC PVC PROBE 1500 mm
2-wire probe temperature range $-30^{\circ}+80^{\circ}\text{C}$
bulb \varnothing 6x40 mm



3445107 PTC PVC PROBE 3000 mm
2-wire probe temperature range $-30^{\circ}+80^{\circ}\text{C}$
bulb \varnothing 6x40 mm





Suitable for:

Electronic thermostats and controllers



3445110 TRANSFORMER 230V/12V 3VA
 primary tension 230Vca 50/60Hz
 secondary tension 12Vca 3VA
 room temperature 0÷60°C
 screw terminal block
 IMQ approved



3445111 TRANSFORMER 24V/12V 3VA
 primary tension 24Vca 50/60Hz
 secondary tension 12Vca 3VA
 room temperature 0÷60°C
 screw terminal block
 IMQ approved



3445154 PROBE NTC IP68 3000 mm
 temperature range -40°+110°C
 bulb ø 6x40 mm watertight



3445155 SILICONE PROBE NTC 3000 mm
 temperature range -50°+110°C
 bulb ø 6x40 mm



3445156 PROBE NTC PVC 3000 mm
 temperature range -30°+80°C
 bulb ø 6x40 mm



3445157 PROBE NTC PVC 1500 mm
 temperature range -30°+80°C
 bulb ø 6x40 mm



3445167 PROBE NTC IP68 1500 mm
 temperature field -50°+110°C
 bulb ø 6x20 mm watertight



3445183 SILICONE PTC PROBE 3000 mm
 2-wire probe temperature range -55+150°C
 bulb ø 6x40 mm



3445184 PROBE NTC PVC 1500 mm IP68
 temperature range -40°+110°C
 bulb ø 6x40 mm watertight



3445335 PROBE NTC IP68 3000 mm
 temperature range -50+110°C
 bulb ø 6x15 mm watertight





Electronic thermostats and controllers



Suitable for:

3445379 PROBE PT1000 PVC 1500 mm IP68
temperature range $-50^{\circ}+110^{\circ}\text{C}$
bulb \varnothing 6x20 mm watertight



Suitable for:

3445380 PROBE PT1000 PVC 3000 mm IP68
temperature range $-50^{\circ}+110^{\circ}\text{C}$
bulb \varnothing 6x20 mm watertight



3445913 SILICONE PROBE NTC 1500 mm
temperature range $-50+110^{\circ}\text{C}$
bulb \varnothing 6x40 mm



3445959 SILICONE PTC PROBE 5000 mm
temperature range $-55^{\circ}+150^{\circ}\text{C}$
bulb \varnothing 6x40 mm



3445378 CONTROLLER ELIWELL ID PLUS 974
230V 50/60Hz
1 relay output 2Hp for compressor
1 relay output 8A for defrosting
1 relay output 5A for fans
2 selectable NTC/PTC/PT1000 probes (not included)
1 programmable digital/temperature input
1 programmable digital input
TTL input for copy card connection
with buzzer
front dimension 74x32xdepth 59 mm
mounting hole 71x29 mm



3445028 PROBE NTC PVC 4000 mm
temperature field $-30^{\circ}+80^{\circ}\text{C}$
bulb \varnothing 6x20 mm



3445070 PTC PVC PROBE 1500 mm
2-wire probe temperature range $-30+80^{\circ}\text{C}$
bulb \varnothing 6x40 mm



3445107 PTC PVC PROBE 3000 mm
2-wire probe temperature range $-30+80^{\circ}\text{C}$
bulb \varnothing 6x40 mm



3445154 PROBE NTC IP68 3000 mm
temperature range $-40^{\circ}+110^{\circ}\text{C}$
bulb \varnothing 6x40 mm watertight



3445155 SILICONE PROBE NTC 3000 mm
temperature range $-50^{\circ}+110^{\circ}\text{C}$
bulb \varnothing 6x40 mm





Electronic thermostats and controllers



Suitable for:

3445156 PROBE NTC PVC 3000 mm
temperature range $-30^{\circ}+80^{\circ}\text{C}$
bulb \varnothing 6x40 mm



Suitable for:

3445157 PROBE NTC PVC 1500 mm
temperature range $-30^{\circ}+80^{\circ}\text{C}$
bulb \varnothing 6x40 mm



3445167 PROBE NTC IP68 1500 mm
temperature field $-50^{\circ}+110^{\circ}\text{C}$
bulb \varnothing 6x20 mm watertight



3445183 SILICONE PTC PROBE 3000 mm
2-wire probe temperature range $-55^{\circ}+150^{\circ}\text{C}$
bulb \varnothing 6x40 mm



3445184 PROBE NTC PVC 1500 mm IP68
temperature range $-40^{\circ}+110^{\circ}\text{C}$
bulb \varnothing 6x40 mm watertight



3445335 PROBE NTC IP68 3000 mm
temperature range $-50^{\circ}+110^{\circ}\text{C}$
bulb \varnothing 6x15 mm watertight



3445379 PROBE PT1000 PVC 1500 mm IP68
temperature range $-50^{\circ}+110^{\circ}\text{C}$
bulb \varnothing 6x20 mm watertight



3445380 PROBE PT1000 PVC 3000 mm IP68
temperature range $-50^{\circ}+110^{\circ}\text{C}$
bulb \varnothing 6x20 mm watertight



3445913 SILICONE PROBE NTC 1500 mm
temperature range $-50^{\circ}+110^{\circ}\text{C}$
bulb \varnothing 6x40 mm



3445959 SILICONE PTC PROBE 5000 mm
temperature range $-55^{\circ}+150^{\circ}\text{C}$
bulb \varnothing 6x40 mm





Electronic thermostats and controllers



Suitable for:

Suitable for:

3445390 CONTROLLER DIXELL XR70CX-5N0C3
 230V 50/60Hz
 1 relay output 16A for compressor
 1 relay output 5A for ventilator
 1 relay output 8A for defrosting
 1 relay output 8A for light/alarm
 2 selectable NTC/PTC probes (not included)
 1 programmable digital input
 front dimension 78x37 depth 60 mm
 mounting hole 71x29 mm



3445070 PTC PVC PROBE 1500 mm
 2-wire probe temperature range -30+80°C
 bulb ø 6x40 mm



3445157 PROBE NTC PVC 1500 mm
 temperature range -30°+80°C
 bulb ø 6x40 mm



3445399 CONTROLLER ELIWELL ID PLUS 902
 12Vac/dc
 1 relay output 8A for compressor
 1 selectable NTC/PTC/PT1000 probe (not included)
 1 programmable digital/temperature input
 TTL input for copy card connection
 front dimension 74x32x59 mm
 mounting hole 71x29 mm



3445028 PROBE NTC PVC 4000 mm
 temperature field -30°+80°C
 bulb ø 6x20 mm



3445070 PTC PVC PROBE 1500 mm
 2-wire probe temperature range -30+80°C
 bulb ø 6x40 mm



3445107 PTC PVC PROBE 3000 mm
 2-wire probe temperature range -30+80°C
 bulb ø 6x40 mm



3445154 PROBE NTC IP68 3000 mm
 temperature range -40°+110°C
 bulb ø 6x40 mm watertight



3445155 SILICONE PROBE NTC 3000 mm
 temperature range -50°+110°C
 bulb ø 6x40 mm





Suitable for:

Electronic thermostats and controllers



3445156 PROBE NTC PVC 3000 mm
temperature range $-30^{\circ}+80^{\circ}\text{C}$
bulb \varnothing 6x40 mm



3445157 PROBE NTC PVC 1500 mm
temperature range $-30^{\circ}+80^{\circ}\text{C}$
bulb \varnothing 6x40 mm



3445167 PROBE NTC IP68 1500 mm
temperature field $-50^{\circ}+110^{\circ}\text{C}$
bulb \varnothing 6x20 mm watertight



3445183 SILICONE PTC PROBE 3000 mm
2-wire probe temperature range $-55^{\circ}+150^{\circ}\text{C}$
bulb \varnothing 6x40 mm



3445184 PROBE NTC PVC 1500 mm IP68
temperature range $-40^{\circ}+110^{\circ}\text{C}$
bulb \varnothing 6x40 mm watertight



3445335 PROBE NTC IP68 3000 mm
temperature range $-50^{\circ}+110^{\circ}\text{C}$
bulb \varnothing 6x15 mm watertight



3445379 PROBE PT1000 PVC 1500 mm IP68
temperature range $-50^{\circ}+110^{\circ}\text{C}$
bulb \varnothing 6x20 mm watertight



3445380 PROBE PT1000 PVC 3000 mm IP68
temperature range $-50^{\circ}+110^{\circ}\text{C}$
bulb \varnothing 6x20 mm watertight



3445913 SILICONE PROBE NTC 1500 mm
temperature range $-50^{\circ}+110^{\circ}\text{C}$
bulb \varnothing 6x40 mm



3445959 SILICONE PTC PROBE 5000 mm
temperature range $-55^{\circ}+150^{\circ}\text{C}$
bulb \varnothing 6x40 mm






Electronic thermostats and controllers



Suitable for:

Suitable for:

3445400 CONTROLLER ELIWELL ID PLUS 961
 12Vac/dc
 1 relay output 2Hp for compressor
 1 selectable NTC/PTC/PT1000 probe (not included)
 1 programmable digital/temperature input
 pause defrosting
 TTL input for copy card connection
 front dimension 74x32xdepth 59 mm
 mounting hole 71x29 mm



3445028 PROBE NTC PVC 4000 mm
 temperature field -30°+80°C
 bulb ø 6x20 mm



3445070 PTC PVC PROBE 1500 mm
 2-wire probe temperature range -30+80°C
 bulb ø 6x40 mm



3445107 PTC PVC PROBE 3000 mm
 2-wire probe temperature range -30+80°C
 bulb ø 6x40 mm



3445154 PROBE NTC IP68 3000 mm
 temperature range -40°+110°C
 bulb ø 6x40 mm watertight



3445155 SILICONE PROBE NTC 3000 mm
 temperature range -50°+110°C
 bulb ø 6x40 mm



3445156 PROBE NTC PVC 3000 mm
 temperature range -30°+80°C
 bulb ø 6x40 mm



3445157 PROBE NTC PVC 1500 mm
 temperature range -30°+80°C
 bulb ø 6x40 mm



3445167 PROBE NTC IP68 1500 mm
 temperature field -50°+110°C
 bulb ø 6x20 mm watertight



3445183 SILICONE PTC PROBE 3000 mm
 2-wire probe temperature range -55+150°C
 bulb ø 6x40 mm





Electronic thermostats and controllers



Suitable for:

3445184 PROBE NTC PVC 1500 mm IP68
temperature range $-40^{\circ}+110^{\circ}\text{C}$
bulb \varnothing 6x40 mm watertight



Suitable for:

3445335 PROBE NTC IP68 3000 mm
temperature range $-50^{\circ}+110^{\circ}\text{C}$
bulb \varnothing 6x15 mm watertight



3445379 PROBE PT1000 PVC 1500 mm IP68
temperature range $-50^{\circ}+110^{\circ}\text{C}$
bulb \varnothing 6x20 mm watertight



3445380 PROBE PT1000 PVC 3000 mm IP68
temperature range $-50^{\circ}+110^{\circ}\text{C}$
bulb \varnothing 6x20 mm watertight



3445913 SILICONE PROBE NTC 1500 mm
temperature range $-50^{\circ}+110^{\circ}\text{C}$
bulb \varnothing 6x40 mm



3445959 SILICONE PTC PROBE 5000 mm
temperature range $-55^{\circ}+150^{\circ}\text{C}$
bulb \varnothing 6x40 mm



3445401 CONTROLLER ELIWELL ID PLUS 971
12Vac/dc
1 relay output 2Hp for compressor
1 relay output 8A for defrosting
2 selectable NTC/PTC/PT1000 probes (not included)
1 programmable digital/temperature input
1 programmable digital input
TTL input for copy card connection
with buzzer
front dimension 74x32xdepth 59 mm
mounting hole 71x29 mm



3445028 PROBE NTC PVC 4000 mm
temperature field $-30^{\circ}+80^{\circ}\text{C}$
bulb \varnothing 6x20 mm



3445070 PTC PVC PROBE 1500 mm
2-wire probe temperature range $-30^{\circ}+80^{\circ}\text{C}$
bulb \varnothing 6x40 mm



3445107 PTC PVC PROBE 3000 mm
2-wire probe temperature range $-30^{\circ}+80^{\circ}\text{C}$
bulb \varnothing 6x40 mm





Electronic thermostats and controllers



Suitable for:

3445154 PROBE NTC IP68 3000 mm
temperature range $-40^{\circ}+110^{\circ}\text{C}$
bulb \varnothing 6x40 mm watertight



Suitable for:

3445155 SILICONE PROBE NTC 3000 mm
temperature range $-50^{\circ}+110^{\circ}\text{C}$
bulb \varnothing 6x40 mm



3445156 PROBE NTC PVC 3000 mm
temperature range $-30^{\circ}+80^{\circ}\text{C}$
bulb \varnothing 6x40 mm



3445157 PROBE NTC PVC 1500 mm
temperature range $-30^{\circ}+80^{\circ}\text{C}$
bulb \varnothing 6x40 mm



3445167 PROBE NTC IP68 1500 mm
temperature field $-50^{\circ}+110^{\circ}\text{C}$
bulb \varnothing 6x20 mm watertight



3445183 SILICONE PTC PROBE 3000 mm
2-wire probe temperature range $-55+150^{\circ}\text{C}$
bulb \varnothing 6x40 mm



3445184 PROBE NTC PVC 1500 mm IP68
temperature range $-40^{\circ}+110^{\circ}\text{C}$
bulb \varnothing 6x40 mm watertight



3445335 PROBE NTC IP68 3000 mm
temperature range $-50+110^{\circ}\text{C}$
bulb \varnothing 6x15 mm watertight



3445379 PROBE PT1000 PVC 1500 mm IP68
temperature range $-50^{\circ}+110^{\circ}\text{C}$
bulb \varnothing 6x20 mm watertight



3445380 PROBE PT1000 PVC 3000 mm IP68
temperature range $-50^{\circ}+110^{\circ}\text{C}$
bulb \varnothing 6x20 mm watertight



3445913 SILICONE PROBE NTC 1500 mm
temperature range $-50+110^{\circ}\text{C}$
bulb \varnothing 6x40 mm



3445959 SILICONE PTC PROBE 5000 mm
temperature range $-55^{\circ}+150^{\circ}\text{C}$
bulb \varnothing 6x40 mm





Electronic thermostats and controllers



Suitable for:

Suitable for:

3445402 CONTROLLER ELIWELL ID PLUS 974
 12Vac/dc
 1 relay output 2Hp for compressor
 1 relay output 8A for defrosting
 1 relay output 5A for fans
 2 selectable NTC/PTC/PT1000 probes (not included)
 1 programmable digital/temperature input
 1 programmable digital input
 TTL input for copy card connection
 with buzzer
 front dimension 74x32xdepth 59 mm
 mounting hole 71x29 mm



3445028 PROBE NTC PVC 4000 mm
 temperature field -30°+80°C
 bulb ø 6x20 mm



3445070 PTC PVC PROBE 1500 mm
 2-wire probe temperature range -30+80°C
 bulb ø 6x40 mm



3445107 PTC PVC PROBE 3000 mm
 2-wire probe temperature range -30+80°C
 bulb ø 6x40 mm



3445154 PROBE NTC IP68 3000 mm
 temperature range -40°+110°C
 bulb ø 6x40 mm watertight



3445155 SILICONE PROBE NTC 3000 mm
 temperature range -50°+110°C
 bulb ø 6x40 mm



3445156 PROBE NTC PVC 3000 mm
 temperature range -30°+80°C
 bulb ø 6x40 mm



3445157 PROBE NTC PVC 1500 mm
 temperature range -30°+80°C
 bulb ø 6x40 mm



3445167 PROBE NTC IP68 1500 mm
 temperature field -50°+110°C
 bulb ø 6x20 mm watertight



3445183 SILICONE PTC PROBE 3000 mm
 2-wire probe temperature range -55+150°C
 bulb ø 6x40 mm





Electronic thermostats and controllers



Suitable for:

3445184 PROBE NTC PVC 1500 mm IP68
temperature range $-40^{\circ}+110^{\circ}\text{C}$
bulb \varnothing 6x40 mm watertight



Suitable for:

3445335 PROBE NTC IP68 3000 mm
temperature range $-50^{\circ}+110^{\circ}\text{C}$
bulb \varnothing 6x15 mm watertight



3445379 PROBE PT1000 PVC 1500 mm IP68
temperature range $-50^{\circ}+110^{\circ}\text{C}$
bulb \varnothing 6x20 mm watertight



3445380 PROBE PT1000 PVC 3000 mm IP68
temperature range $-50^{\circ}+110^{\circ}\text{C}$
bulb \varnothing 6x20 mm watertight



3445913 SILICONE PROBE NTC 1500 mm
temperature range $-50^{\circ}+110^{\circ}\text{C}$
bulb \varnothing 6x40 mm



3445959 SILICONE PTC PROBE 5000 mm
temperature range $-55^{\circ}+150^{\circ}\text{C}$
bulb \varnothing 6x40 mm

